

**KKM**Three-phase hermetically sealed type  
oil-immersed shunt reactor  
2000(1000)kVAr, 20.5kV, YN**FINAL****TECHNICAL DATA**

1.	Manufacturer		KKM Power d.o.o, Serbia
2.	Reactor type		Oil-immersed, hermetically sealed type
3.	Reactor kind		Shunt reactor, for compensation
4.	Standard		IEC 60076-6 (Clause 7)
5.	Reactor name		<b>SSHR2 2000-20.5-0,7</b>
6.	Rated power	[kVAr]	2000 (1000)
7.	Number of phases		3
8.	Rated frequency	[Hz]	50
9.	Highest voltage of equipement	[kV]	24
10.	Insulation level	[kV]	LI 125/AC 50
11.	Rated voltage	[kV]	20.5
12.	Maximum operating voltage	[kV]	22
13.	Winding connection		YN
14.	Rated current	[A]	56.33 (28.17)
15.	Winding material	Cu/Al	Aluminium
16.	Tap changer	Yes/No	Yes, with two taps: 2000kVAr, 1000kVAr
17.	Total losses at 75°C	[W]	<14000 (<7000)
18.	Type of cooling		ONAN
19.	Instalation altitude	[m]	<1000
20.	Minimum/Maximum temperature of ambient	[°C]	-40/40
21.	Maximum temperature rise of winding	[K]	65
22.	Maximum temperature rise of oil	[K]	60
23.	Thermal class of insulation		A
24.	Instalation conditions		Outdoor/Indoor
25.	Anti-corrosive protection		Hot-dip galvanizing
26.	Approximate length of reactor	[mm]	2048
27.	Approximate width of reactor	[mm]	1165
28.	Approximate height of reactor	[mm]	2190
29.	Mass of oil in reactor	[kg]	1535
30.	Total mass of reactor	[kg]	5875

<b>KKM</b>	<b>Three-phase hermetically sealed type oil-immersed shunt reactor 2000(1000)kVAr, 20.5kV, YN</b>	<b>FINAL</b>
31.	Accessories	<ol style="list-style-type: none"> <li>1. Terminals: Phases: Plug-in 36kV, 630A Neutral: Plug-in 36kV, 630A</li> <li>2. Protection relay: R.I.S.</li> <li>3. Pt100 probe</li> </ol>

Date: 24.04.2018